

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
7 September 2001 (07.09.2001)

PCT

(10) International Publication Number
WO 01/65857 A1

- (51) International Patent Classification⁷: **H04N 7/26** (74) Agent: **LANDOUSY, Christian**; Internationaal Octrooibureau B.V., Prof Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (21) International Application Number: **PCT/EP01/01965**
- (22) International Filing Date: **21 February 2001 (21.02.2001)** (81) Designated States (*national*): **JP, KR.**
- (25) Filing Language: **English** (84) Designated States (*regional*): **European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).**
- (26) Publication Language: **English**
- (30) Priority Data:
00400551.8 **29 February 2000 (29.02.2000)** **EP** Published:
— *with international search report*
- (71) Applicant: **KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]**; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.
- (72) Inventor: **DEL CORSO, Sandra**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(54) Title: **FILM SOURCE VIDEO DETECTION AND ENCODING**



(57) Abstract: The invention relates to a method for encoding video signals corresponding to a sequence of frames constituted either from video-type images or film-type images. These film-type images are obtained by means of the 3 : 2 pull-down technique involving a subdivision of each film frame into two fields and a duplication of two fields within each group of four subdivided frames. According to the invention, the encoding step of the signals is preceded by a preprocessing step that comprises the sub-steps of : (A) thresholding the eight absolute values of the successive pixel-to-pixel differences between fields of the same parity ; (B) measuring the density of "1" (resp."0") per block of $m \times n$ pixels of the field structure, said measure leading to mark each pixel as 1 or 0 ; (C) detecting in any group of ten successive fields within the preprocessed signals thus obtained, the film pattern formed by said duplicated fields ; (D) switching said preprocessed signals from a first encoding mode to a second one, when said film pattern is detected, or from the second one to the first one, when it is not detected ; (E) encoding said switched signals according to the first mode or to the second mode.

WO 01/65857 A1

FILM SOURCE VIDEO DETECTION AND ENCODING

FIELD OF THE INVENTION

The present invention relates to a method for encoding video signals corresponding to a sequence of frames constituted either of video-type images, at the video format of 30 interlaced frames per second, or film-type images, converted from an original frame rate of 24 Hz to said video type format by means of the 3 : 2 pull-down technique involving a subdivision of each film frame into two fields and a duplication of two fields within each group of four subdivided frames. It also relates to an encoding device for carrying out said method. This invention may be used for instance when encoding according to the MPEG-2 standard image sequences which include both movies, at 24 Hz, and NTSC video images (30 interlaced frames per second).

BACKGROUND OF THE INVENTION

In the NTSC standard, the picture frequency is 30 interlaced frames per second. However, for movies (that are inherently progressive), the progressive frames are produced at a frame rate of 24 Hz. Displaying a sequence of film-type images (originally at 24 frames) on television, at NTSC rates of 60 video fields per second, therefore requires a conversion process called "3:2 pull-down". This technique, described for instance in the international patent application W0 97/39577, consists of creating five interlaced frames (which can be therefore visualized on television) based on four original sequential (or : progressive) film frames. This is obtained by dividing each of these four sequential frames by two, so as to form four odd and four even fields, and by duplicating two of these eight fields.

As illustrated in Fig.1, which shows an original film sequence at 24 Hz on the first line and illustrates on the second line how to organize the field sequencing of a video sequence at 30 Hz corresponding to said film sequence, it means that an additional field is inserted for each pair of film frames, for instance by splitting one film frame out of two into three fields, the other one being split as usually into two fields. In the case of the frame split into three fields (for instance, G1G2 split into F1, F2, F3, or G5G6 split into F6, F7, F8), the third one is obtained by copying the odd (F1) or the even field (F6) alternately, in order to keep the sequencing "odd/even". The result is the following (conditions CD1) :

F1 = F3 = G1
 F2 = G2
 F4 = G4
 F5 = G3
 5 F6 = F8 = G6
 F7 = G5
 F9 = G7
 F10 = G8, and so on.

10 These two additional fields obtained by duplication constitute a redundant information. When encoding such sequences according to the MPEG-2 standard, it is interesting to detect said information : the suppression of these repeated fields frees some space to better encode the other ones, the concerned MPEG-2 encoder thus receiving both video-type image sequences at 30 Hz and original film-type image sequences at 24 Hz.

15 An usual criterion to detect automatically sequences coming from movies (film-type image sequences) is therefore the following : a structure of five frames - i.e. of ten fields - is analyzed by means of a subtraction of consecutive fields of the same parity. The conditions to detect the 3:2 pull-down structure (i.e. to detect in any group of ten successive fields the specific film pattern formed by the two duplicated fields) are the following (conditions CD2) :

20 F1 = F3
 F2 ≠ F4
 F3 ≠ F5
 F4 ≠ F6
 F5 ≠ F7
 25 F6 = F8
 F7 ≠ F9
 F8 ≠ F10,

30 as depicted in the sequence of Fig.2 showing how fields are sequenced for the film mode format and illustrating the set of tests (identical ? or not ?) to be carried out for the detection of a 3:2 pull-down structure (f1, f2,... designate the successive frames, 1o-1e, 1o-2e, 2o-3e,... the corresponding pairs of fields, y the reply "yes" to the test of comparison, i.e. fields equal, and n the reply "no", i.e. fields different). If all these conditions are satisfied, then the inverse 3:2 pull-down conversion (suppression of the two repeated fields) is performed on the

corresponding group of five frames ; on the contrary, if one of these conditions is not valid, the encoder goes back to the video mode (no elimination of the repeated fields).

However, due to the possible presence of noise on the original 3:2 pull-down sequence, the equality criterion between two fields (F1, F3 and F6, F8) may be not strictly verified. Two fields of the same parity $F(N)$ and $F(N+2)$ are considered. If NTOT designates the total number of pixels in a field (172800 for a full resolution), $val(F(N))$ designates the luminance value for a given pixel, $N1$ is the number of picture elements (pixels) such as $ABS[val(F(N)) - val(F(N+2))] > THRES1$, Nm is the number of pixels such as $ABS[val(F(N)) - val(F(N+2))] < THRES2$, $N2$ is the number of pixels such as $N2 = NTOT - Nm$, and $THRES1$, $THRES2$ are predetermined thresholds, then the following test, the values of Ratio 1 and Ratio 2 being previously chosen, is carried out :

IF $((N1 < \text{Ratio 1}) \text{ and } (N2 < \text{Ratio 2}))$ THEN : $F(N) = F(N+2)$
 ELSE : $F(N) \neq F(N+2)$

The first criterion ($N1 < \text{Ratio 1}$) may be called "the dissimilarity criterion" and involves the number of pixels where the field-to-field pixel difference is large, while the second one ($N2 < \text{Ratio 2}$) may be called "the likeness criterion" and involves the number of pixels where the field-to-field pixel difference is small.

Troubles within the film mode detection step may consequently occur, mostly in the case of the two following contrasted situations. For static or quasi-static sequences, the dissimilarity criterion is no longer verified, since the fields are nearly all equal. Said criterion is therefore suppressed, the residual conditions needed to be fulfilled being then only $F1 = F3$ and $F6 = F8$ (conditions CD2). But, for a very noisy sequence, with which two identical fields may however seem unlike, the threshold setting the likeness criterion cannot be too increased, otherwise fields that are different could be considered as identical.

The european patent application, previously filed by the applicant under the number 99403228.2 (PHF99621), describes an encoding method (and also a corresponding encoding device) including a film mode detection step with which the above-indicated drawback is now avoided. According to said document, when dealing with noisy images, the criterion for detecting automatically sequences coming from movies is modified on the basis of the following remark. By looking at the $N2$ statistics, the applicant has noticed that $N2$ for fields F1 and F3 (referenced $N2[1,3]$) and $N2$ for fields F6 and F8 (referenced $N2[6,8]$) are small compared to the others (more generally, $N2[i,j]$ stands for statistics of $N2$ calculated for $Fj-Fi$). Then, by computing the difference between two consecutive $N2$ statistics, for instance : $N2[6,8] - N2[5,7]$, and comparing - in the form of a percentage - said difference to a

predetermined threshold (according to an expression of the following form : $N2[5,7]-N2[6,8] \times 100/NTOT$ for example), a large value of percentage is obtained every five computations. Therefore, if the computed percentage is less than X %, with for instance $X = 30 \%$, both fields (of the last considered pair of fields) are considered as equal, and the inverse 3:2 pull-down processing is carried out for the next five frames.

An encoding device in which this preprocessing operation is included is described with reference to Fig.3 and comprises means 31 for encoding input signals corresponding to input sequences either coming from movies or of video type, means for detecting in the input signals of the encoding device a sequence of film type, and means 33 for switching, only when such a detection has occurred, from a first to a second mode of operation of the encoding means 31 (encoding means 31 are located downstream of said switching means).

The encoding means 31 comprise in series a suppressing stage 311 and a coding stage 312, for instance an MPEG-2 coder. The detecting means consists of a detecting stage 32, illustrated in a more detailed manner in Fig.4 and comprising first a set of subtractors 41.1, 41.2, 41.3,..., provided for receiving each one two successive fields of the same parity and determining per pixel the difference between these fields. These subtractors are followed by a set of circuits 42.1, 42.2, 42.3,... provided for taking the absolute value of said difference ; this value is stored in a memory, 43.1, 43.2, 43.3,..., respectively. The successive differences between the successive values of these stored absolute values are then computed in subtractors 44.1, 44.2, 44.3,..., and these differences, for instance multiplied by $100/NTOT$ as indicated above, are compared to the predefined threshold (comparison tests C1). If the fields can be considered as equal (results "TRUE" of the tests : $F1 = F3$, and $F6 = F8$), the conditions previously called CD2 are satisfied, and the inverse 3:2 pull-down processing is performed on the next group of five frames, in the suppressing stage 311. In the other cases (i.e. if one of the conditions CD2 is no more valid, which corresponds to a result "FALSE" of the tests) , the switching means 33 are in the opposite position, and the stage 311 is de-activated : the encoding stage goes back to the video mode (no elimination of the repeated fields : the input of the encoding device is directly connected to the input of the coding stage 312).

In the video sequences now currently handled, one or several objects coded according to the film mode may however be present, and it may then be necessary to detect these objects. As each object can be of any shape and have any random position within the considered successive images, it becomes no longer possible to use the previously described

solution (i.e. a detection that is done using some pixel statistics from the complete image), since the film mode coded object(s) size and position within any image are unknown.

SUMMARY OF THE INVENTION

5 It is therefore an object of the invention to propose an encoding method allowing to solve this problem.

To this end, the invention relates to a method such as defined in the introductory part of the description and which is moreover characterized in that the encoding step of said signals is preceded by a preprocessing step, itself including the sub-steps of :

10 (A) thresholding the eight absolute values of the successive pixel-to-pixel differences between fields of the same parity for each group of ten successive fields within said input signals, each pixel being marked as 1 (resp.0) when the corresponding absolute value is equal to or greater than a first predefined threshold or as 0 (resp.1) when said absolute value is lower than said first threshold ;

15 (B) measuring the density of "1" (resp."0") per block of $m \times n$ pixels of the field structure, said density being computed for each of said blocks by means of a comparison, to a second predefined threshold, of the ratio between the number of bits at 1 in each block and the average number of bits at 1 in all the blocks, each pixel being marked as 1 (resp.0) when said ratio is equal to or greater than said second threshold or as 0 (resp.1) when
20 said ratio is lower than said second threshold ;
said preprocessing step being followed by the steps of :

(C) detecting in any group of ten successive fields within the preprocessed signals thus obtained, the film pattern formed by said duplicated fields ;

(D) switching said preprocessed signals from a first encoding mode to a
25 second one, when said film pattern is detected, or from the second one to the first one, when it is not detected ;

and the encoding step being such that said switched signals are coded according to the first mode or to the second mode, said first mode corresponding to the coding of sequences of video type and said second one to the coding of sequences in which the fields introduced by
30 duplication have been eliminated.

It is another object of the invention to propose an encoding device allowing to implement said encoding method.

To this end, the invention relates to a device for encoding video signals corresponding to a sequence of frames constituted either from video-type images, at the video

format of 30 interlaced frames per second, or film-type images, converted from an original frame rate of 24 Hz to said video type format by means of the 3 : 2 pull-down technique involving a subdivision of each film frame into two fields and a duplication of two fields within each group of four subdivided frames, characterized in that said device comprises :

- 5 (A) means for encoding input signals corresponding to input sequences either coming of film-type or of video type ;
- (B) a stage for detecting in the input signals of the encoding device a sequence of film-type ;
- (C) means for switching, only when such a detection by means of said
- 10 detecting stage has occurred, from a first output corresponding to a first mode of operation of said encoding means to a second output corresponding to a second mode of operation of said encoding means, or switching from said second output to the first one when said detection no longer occurs, said first mode corresponding to the coding of sequences of video type and said second one to the coding of sequences in which the fields duplicated according to the 3 :
- 15 2 pull-down technique have been eliminated.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will now be described, by way of example, with reference to the accompanying drawings in which :

- 20 - Fig.1 illustrates the 3:2 pull-down technique allowing to construct five interlaced frames from four original sequential frames ;
- Fig.2 shows how fields are sequenced in the film mode format and illustrates a set of tests (identical ? or not ?) to be carried out for the detection of a 3:2 pull-down structure ;
- 25 - Fig.3 shows an encoding device in which the method according to the european patent application previously cited is implemented ;
- Fig.4 is an implementation of a preprocessing device comprised in the encoding device of Fig.3 ;
- Fig.5 illustrates an example of preprocessing device for the implementation
- 30 of the preprocessing step according to the invention ;
- Fig.6 gives some examples of pseudo-median filters ;
- Fig.7 shows an encoding device which comprises a preprocessing device according to the invention.

DETAILED DESCRIPTION OF THE INVENTION

The method according to the invention has for object to implement an encoding method in which a preprocessing operation is provided for weakening the effect of noise. As said hereinabove, it is observed that, every five differences between fields of the same parity, the absolute value at the pixel position where the object is displayed in film mode is theoretically (when there is no noise) equal to zero : pixels should be exactly identical. Due to noise, this equality criterion is no longer strictly verified : the method now proposed will allow to discriminate identical pixels and dissimilar ones.

According to the preprocessing device 72 of Fig.5 showing an example of implementation of said method, a circuit 51 is first provided for carrying out a thresholding step applied on each absolute pixel-to-pixel field difference $F[i+2] - F[i]$. If an absolute value of the field difference is equal to or greater than a predefined threshold T1, the pixel is marked as 1, which corresponds (for instance) to pixels not considered as equal. If said absolute value is lower than this threshold, the pixels are marked as 0 and considered as equal.

A circuit 62 may be provided for implementing after said thresholding step an additional step intended to optimize the thresholded picture. The optimizing circuit 62 is in the present case a so-called pseudo-median filter which modifies or not the value 0 or 1 of each pixel according to the values of the neighbouring pixels and its own value considered together. The decision of modifying or not the value is for instance taken according to the following relations (1) and (2), as illustrated in Fig.6 that shows some examples of pseudo-median filtering decisions :

$$\text{if } [(NBNP < a) \text{ and } (VP = 1)], VP = 0 \quad (1)$$

$$\text{if } [(NBNP > b) \text{ and } (VP = 0)], VP = 1 \quad (2)$$

where NBNP is the number of neighbouring pixels marked as 1 after the first thresholding step, VP is the value of the considered pixel (to which the pseudo-median filtering step is applied), and a, b are in the present example equal to 3 and 5 respectively.

A step of measure of density is then carried out in a circuit 53, for instance on 4×2 windows within the field structure. An average number of "1" per " 4×2 " block, called ANB1, is first calculated :

$$ANB1 = NBTB1/NB42B \quad (3)$$

where NBTB1 is the total number of bits equal to 1 and NB42B is the number of " 4×2 " blocks. The percentage of "1" is calculated in each case, compared to the average number of

"1". If this percentage is equal to or greater than a predefined threshold T2 (second thresholding step, carried out by a circuit 54), the pixels within the considered "4 x 2" block are all set to 1, while they are set to 0 when said percentage is smaller than T2. This test for each block may be written (NBB1/BL being the number of bits at 1 in each "4 x 2" block) :

- if $((NBB1/BL) \times 100)/(ANB1) \geq T2$, the pixels within the considered blocks are marked as 1 and edited in film mode.

- else : said pixels are marked as 0.

When following the complete preprocessing operations thus shown in Fig.5, it is now possible to recognize the film mode pixels (i.e. the pixels belonging to the object(s) edited in film mode). The detection of said film mode is based, as already illustrated in Fig.2, on the analysis of a group of five frames (or ten fields), done individually for each pixel : if all the conditions CD2 are fulfilled (the equality being strictly verified), then the pixel is detected and marked as being coded in film mode. A pseudo-median filtering step, carried out by a circuit 65 identical to the circuit 62, may be provided in order to remove the possible small error in the detection operation (such a pseudo-median filtering step may also be carried out just after the density measuring step).

An encoding device in which the preprocessing device 72 is implemented is shown in Fig.7, encoding means and switching means being identical to those of Fig.3 and therefore designated by the same references. In said figure, switching means 33 are provided for switching, only when a detection of an object of film type in the video sequence has occurred, from a first mode of operation, in which the two repeated fields of the 3:2 pull-down structure are eliminated by means of the suppressing stage 311, to a second one corresponding to a direct connection from the input of the encoding device to the input of the coding stage 312 (this coding stage being, as in Fig.3, located downstream of said switching means).

CLAIMS:

1. A method for encoding video signals corresponding to a sequence of frames constituted either of video-type images, at the video format of 30 interlaced frames per second, or film-type images, converted from an original frame rate of 24 Hz to said video type format by means of the 3 : 2 pull-down technique involving a subdivision of each film frame into two fields and a duplication of two fields within each group of four subdivided frames, characterized in that the encoding step of said signals is preceded by a preprocessing step which comprises the sub-steps of :
- 5 (A) thresholding the eight absolute values of the successive pixel-to-pixel differences between fields of the same parity for each group of ten successive fields within said input signals, each pixel being marked as 1 (resp.0) when the corresponding absolute value is equal to or greater than a first predefined threshold or as 0 (resp.1) when said absolute value is lower than said first threshold ;
- 10 (B) measuring the density of "1" (resp."0") per block of $m \times n$ pixels of the field structure, said density being computed for each of said blocks by means of a comparison, to a second predefined threshold, of the ratio between the number of bits at 1 in each block and the average number of bits at 1 in all the blocks, each pixel being marked as 1 (resp.0) when said ratio is equal to or greater than said second threshold or as 0 (resp.1) when said ratio is lower than said second threshold ;
- 15 said preprocessing step being then followed by the steps of :
- 20 (C) detecting in any group of ten successive fields within the preprocessed signals thus obtained, the film pattern formed by said duplicated fields ;
- (D) switching said preprocessed signals from a first encoding mode to a second one, when said film pattern is detected, or from the second one to the first one, when it is not detected ;
- 25 and the encoding step being such that said switched signals are coded according to the first mode or to the second mode, said first mode corresponding to the coding of sequences of video type and said second one to the coding of sequences in which the fields introduced by duplication have been eliminated.

2. A device for encoding video signals corresponding to a sequence of frames constituted either from video-type images, at the video format of 30 interlaced frames per second, or film-type images, converted from an original frame rate of 24 Hz to said video type format by means of the 3 : 2 pull-down technique involving a subdivision of each film
5 frame into two fields and a duplication of two fields within each group of four subdivided frames, characterized in that said device comprises :



(A) means for encoding input signals corresponding to input sequences either of film-type or of video type ;

10 (B) a stage for detecting in the input signals of the encoding device a sequence of film-type ;



(C) means for switching, only when such a detection by means of said detecting stage has occurred, from a first output corresponding to a first mode of operation of said encoding means to a second output corresponding to a second mode of operation of said encoding means, or switching from said second output to the first one when said detection no
15 longer occurs, said first mode corresponding to the coding of sequences of video type and said second one to the coding of sequences in which the fields duplicated according to the 3 : 2 pull-down technique have been eliminated.


3. An encoding device according to claim 2, wherein said encoding means
20 comprise in series, between a first input and their output, a suppressing stage, provided for eliminating said duplicated fields, and a coding stage, a direct connection being also provided between a second input of said encoding means and the input of said coding stage, and said first and second inputs of the encoding means being connected to the first and second outputs of said switching means.

1/4

FIG.1FIG.2

2/4

FIG.3FIG.7

**FIG. 4**

4/4




FIG.5




FIG.6

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 01/01965

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04N7/26

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 588 668 A (SONY CORP) 23 March 1994 (1994-03-23)	2,3
A	page 6, column 8, line 53 -page 7, column 9, line 23 page 8, column 12, line 41 -page 10, column 15, line 19	1
A	US 5 767 923 A (COLEMAN JR E NORTH) 16 June 1998 (1998-06-16) column 15, line 11 -column 17, line 4	1
A	EP 0 708 564 A (AT & T CORP) 24 April 1996 (1996-04-24) page 5, line 24 -page 7, line 50	1-3

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

8 June 2001

Date of mailing of the international search report

18/06/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Marie-Julie, J-M

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 01/01965

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0588668	A	23-03-1994	JP 6197273 A	15-07-1994
			DE 69325220 D	15-07-1999
			DE 69325220 T	16-12-1999
			EP 0893917 A	27-01-1999
			EP 0893918 A	27-01-1999
			EP 0897241 A	17-02-1999
			US 5835672 A	10-11-1998
			US 5768469 A	16-06-1998
			AT 181197 T	15-06-1999
			AU 672812 B	17-10-1996
			AU 4747893 A	31-03-1994
			CN 1095541 A, B	23-11-1994
			CN 1221287 A	30-06-1999
			CN 1221288 A	30-06-1999
			DE 69325221 D	15-07-1999
			DE 69325221 T	16-12-1999
			EP 1030523 A	23-08-2000
			EP 0588669 A	23-03-1994
			EP 0910213 A	21-04-1999
			HK 1013572 A	23-06-2000
			JP 7099603 A	11-04-1995
			JP 2000341698 A	08-12-2000
			US 5461420 A	24-10-1995
US 5767923	A	16-06-1998	US 6061471 A	09-05-2000
EP 0708564	A	24-04-1996	US 5734419 A	31-03-1998
			CA 2157309 A	22-04-1996
			JP 8214305 A	20-08-1996